




A system reset will clear any programming performed in the vehicle including tach learn. Following a reset, the module will need to be programmed to the vehicle again, and you will need to complete the tach learn procedure.

SYSTEM RESET DOES NOT ERASE A FIRMWARE PROGRAMMED TO THE MODULE, OR ALTER ANY SETTINGS IN THE OPTION MENUS. ANY FIRMWARE OR OPTION CHANGES REQUIRE YOU TO CONNECT THE MODULE TO THE WEB OR A MOBILE DEVICE USING A WEBLINK PROGRAMMER.

- >>  The following procedure resets the module programming to the vehicle. It does not reset any settings configured online.
- 01  Disconnect all connectors from module except the M1 BLACK 8-pin connector and the M4 BLACK 20-pin connector.
- 02  Disconnect the M1 BLACK 8-pin connector and the M4 BLACK 20-pin connector.
- 03  PRESS AND HOLD the module's programming button while connecting the M1 BLACK 8-pin connector and the M4 BLACK 20-pin connector.
- 04  Wait, LED 1 will flash RED. RELEASE programming button.
- 05  LED 1 will turn RED for 2 seconds.

- 06  Module RESET completed.
- 07  Reconnect all connectors.
- 08  Repeat programming procedure.
- >>  Failure to follow procedure may result with a DTC or a CHECK ENGINE error message.